

SAMMYS X-Press Vertical Mount

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	TEST LOAD (LBS)	UL MIN THICK	TEST LOAD (LBS)	FM MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
1/4"	8181922	XP 200	X-Press 200	1146 (22 ga)	185 (Luminaire) 250 (Luminaire)	.027" .056"			.125"	25	125	Metal Deck
3/8"	8150922	XP 20	X-Press 20	1146 (22 ga)	850 (2½" Pipe) 185 (Luminaire) 250 (Luminaire) 283 (Conduit & Cable)	.027" .027" .056" .029"	940 (2" Pipe) 1475 (4" Pipe)	.029" .104"	.125"	25	125	Metal Deck
3/8"	8153922	XP 35	X-Press 35	1783 (16 ga)	1500 (4" Pipe) 85 (Luminaire) 250 (Luminaire) 416 (Conduit & Cable)	.060" .029" .056" .059"	940 (2" Pipe) 1475 (4" Pipe)	.029" .104"	.125"	25	125	Purlin
3/8"	8150922	XP 20	X-Press 20	1146 (22 ga)	850 (2½" Pipe)		Pre-Pour Structural Concrete @ 3000 psi Post-Pour Range II LWC ≤ 35 PCF (lbs/ft³)			25	125	Metal Deck (Pre-Pour) Metal Deck (Post-Pour)

SAMMYS X-Press Swivel Head®

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	TEST LOAD (LBS)	UL MIN THICK	TEST LOAD (LBS)	FM MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
3/8"	8295922	SXP 35	Swivel X-Press 35	1675 (16 ga Vertical) 1558 (89° Off Vertical)	1250 (3-1/2" Pipe) 250 vertical (Luminaire) 80 @ 90° (Luminaire) 500 vertical (Conduit & Cable) 333 @ 89° (Conduit & Cable)	.059"	635 (2" Pipe)	.029"	.125"	25	125	Purlin

SAMMYS X-Press Horizontal Mount

ROD SIZE	PART NUMBER	MODEL	DESCRIPTION	ULTIMATE PULLOUT (LBS)	TEST LOAD (LBS)	TEST LOAD (LBS)	MIN THICK	MAX THICK	BOX QTY	CASE QTY	APPLICATION
3/8"	8293957	SWXP 35	Sidewinder X-Press 35	1798 (16 ga)	1250 (3½" Pipe) 80 (Luminaire) 416 (Conduit & Cable)		.060"	.125"	25	125	Purlin

SAMMYS X-Press Swivels – Seismic Restraint

ROD SIZE	PART NUMBER	MODEL	MIN THICKNESS	MAX THICKNESS	APPLICATION	BOX QTY	CASE QTY	INSTALLATION TOOL
3/8"	8295922	SXP 35	16 ga	1/8"	Purlin	25	125	The SWXP 35 must be installed with UXFIT Tool (Part No. 8194910); pre-drilling required.

SAMMYS Sidewinders for Steel – Seismic Restraint

ROD SIZE	PART NUMBER	MODEL	MIN THICKNESS	MAX THICKNESS	APPLICATION	BOX QTY	CASE QTY	INSTALLATION TOOL
3/8"	8293957	SWXP 35	16 ga.	1/8"	Steel Purlin or Bar Joist	25	125	The SWXP 35 must be installed with UXFIT Tool (Part No. 8194910); pre-drilling required.